

Traffic Control & Phasing

NOTES:

1. LOCATIONS OF SIGNS AND BARRICADES MAY BE ADJUSTED AS DIRECTED BY THE ENGINEER.
2. ALL TRAFFIC CONTROL DEVICES SHOWN, UNLESS OTHERWISE NOTED, SHALL BE FURNISHED, INSTALLED, AND MAINTAINED, REMOVED AND REMAIN THE PROPERTY OF THE CONTRACTOR.
3. ALL SIGNS SHALL CONFORM IN LETTER SIZE AND COLOR AS SPECIFIED IN THE MINNESOTA STANDARD SIGNS MANUAL AND AS DESIGNATED ON THE SPECIAL SIGN DETAIL SHEETS.
4. UNLESS OTHERWISE INDICATED OR ELIMINATED BY THE ENGINEER, ALL SIGNS SHOWN WHICH ARE INDEPENDENTLY MOUNTED SHALL BE ATTACHED TO TWO UPRIGHT POSTS EXTENDED FROM TWO DRIVEN ANCHORS. ALL SHALL CONFORM TO THE HEIGHT REQUIREMENTS OF THE MINNESOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
5. ALL TRAFFIC CONTROL DEVICES SHALL CONFORM TO THE MINNESOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION AND TEMPORARY TRAFFIC CONTROL ZONE LAYOUTS (FIELD MANUAL) LATEST EDITION.
6. ALL TRAFFIC CONTROL DEVICES SHALL HAVE REFLECTIVE SHEETING.

